



TURMOSYNTHGREASE LMI 2

K 2 K -20



Date of issue: 26.05.2015

TURMOSYNTHGREASE LMI 2 is a sealing grease for valves and taps.

Special properties

- High oxidation stability (no resinification, not pasting together)
- Very good adhesion
- Stable to cold and hot water as well as water steam
- Odourless and tasteless
- Neutral towards the foam of beer

Product Characteristics	Value	Dimension	Norm / Standard
Colour	colourless, transparent		
Density at 20°C	0,904	g/cm ³	DIN 51757
Operating temperature range	-20 to 120	°C	
Thickener	inorganic thickener		
Base oil	White oil		
Kin. viscosity of the base oil at 40°C	100	mm ² /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	11,8	mm ² /s	DIN EN ISO 3104
Worked penetration	265 – 295	mm/10	DIN ISO 2137
Consistency class (NLGI)	2		DIN 51818
Dropping point	none	°C	DIN ISO 2176
Resistance to water	0 – 90		DIN 51807

Application

Valves, taps and bearings in the food and beverage industry.
Fittings, beer and air pipes of the drum filling organics.

Packaging units

25 x 100 g tubes, 20 x 400 g cartridges, 6 x 1 kg cans, 5 kg bucket, 15 kg hobbock, 25 kg hobbock, 180 kg drum



126662

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>