


CASSIDA CHAIN OIL 1500 SPRAY

Product Information

Synthetic chain lubricant in spray form for food and beverage processing equipment



CASSIDA CHAIN OIL 1500 SPRAY is a fully synthetic high performance, anti-wear chain oil which has been specially developed for use in machinery used in the food and beverage processing and packaging industry.

It is based on a careful blend of synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food and beverage industry.

Registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to FLT Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

CERTIFICATIONS AND SPECIFICATIONS

- NSF H1
- Kosher
- Halal



PERFORMANCE FEATURES

- Excellent adhesive properties minimise "fling-off" in use and wash-off by both cold and hot water
 - Extends the service life of chains and reduces downtime due to superior wear prevention and corrosion protection, even under wet or aggressive conditions
 - Easily applied – spray directly onto chain
 - Neutral odour and taste
- CASSIDA CHAIN OIL 1500 SPRAY is also available in non-spray form, FLT product code 7583

APPLICATIONS

- Drive and transport chains in the food Industry
- Also intended for use in equipment manufacturing food packaging

OPERATING TEMPERATURES

-10 °C to +140 °C (peak +150 °C)

SEAL AND PAINT COMPATIBILITY

Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

HANDLING AND STORAGE

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +30 °C. Provided that the product has been stored under these conditions we recommend that the product be used within 3 years from the date of manufacture.

TYPICAL CHARACTERISTICS			(Typical for current production before addition of solvent/propellant. Variations in these characteristics may occur.)
			CASSIDA CHAIN OIL 1500 SPRAY
Property	Test Method		
NSF Reg. No.			144791
Colour			Colourless
Density at +15 °C	kg/m ³	ISO 12185	865
Flashpoint	°C	ISO 2592	>200
Pourpoint	°C	ISO 3016	-15
Kin. Visc. at +40 °C	mm ² /s	ISO 3104	1500
Kin. Visc. at +100 °C	mm ² /s	ISO 3104	135
Classification ADR			see MSDS
UN-Number			see MSDS



FUCHS LUBRITECH GMBH
Werner-Heisenberg-Straße 1
67661 Kaiserslautern / Germany
T: +49 (0) 6301 3206-0 / F: +49 (0) 6301 3206-940
www.fuchs-lubritech.com

 A Member of the
FUCHS PETROLUB Group

As far as we know these information reflect the current state of knowledge and our research. They cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check the suitability and be satisfied that the output will be satisfactory. Our products are continually being up-dated. We reserve the right, therefore, to alter the information of this product information at any time and without prior announcement. We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us! E-Mail: cassida.lubricants@fuchs-lubritech.de